

**GENERATORE DI VAPORE INDUSTRIALE
PER SANIFICARE E "STERILIZZARE"
CON VAPORE IN BASSA PRESSIONE
E SERBATOIO INTERNO DI ACQUA**

**INDUSTRIAL STEAM GENERATOR
FOR A COMPLETE SANITIZING AND "STERILIZING"
WITH LOW PRESSURE STEAM
AND INTERNAL WATER TANK**



vaporONE 32.20 AR

- Vapore continuo a temperatura costante
 - Pronto al lavoro in un paio di minuti
 - Vapore testato da "Fondazione Edmund Mach"
 - Serbatoio interno per autonomia di funzionamento
 - PLC per controlli di sicurezza e funzionamento
 - Struttura e pannelli in acciaio inox 304
 - Ruote antitraccia e freno
 - Termoriscaldatori elettrici avvitabili inox 316L
 - Garanzia 6 anni sul corpo caldaia inox 304
- Continuous steam flow at constant temperature,
 - Ready to work in a couple of minutes
 - Steam tested by "Fondazione Edmund Mach"
 - Internal water tank for independent operation
 - Internal PLC controls functions and safety features
 - Stainless steel 304 construction and panels
 - Non-marking wheels + brake
 - Screwable electric heating elements stainless steel 316L
 - 6 years warranty on boiler body stainless steel 304

DATI TECNICI | TECHNICAL DATA

Alimentazioni disponibili (altre a richiesta):
Available power supplies (others on request):

230 V / ~3 / 50-60 Hz / ~51 A
400-415-440-480 V / ~3 / 50-60 Hz / ~29 A

Potenza totale installata:
Power output:

20,2 kW

Potenza motore-pompa:
Power output motor-pump:

0,2 kW

Potenza riscaldamento:
Heating power:

20,0 kW

Pressione vapore (max):
Steam pressure (max):

2,0 bar

Volume vapore (medio):
Steam volume (average):

32 kg/h

Temperatura di entrata acqua (max):
Inlet water temperature (max):

35 °C

Termostato di lavoro:
Work thermostat:

160 °C

Termostato di sicurezza su caldaia:
Safety thermostat on boiler:

170 °C

Temperatura di uscita/esercizio vapore:
Operating steam temperature:

~120 °C

Serbatoio interno acqua:
Internal reserve tank:

~25 l

Livello acustico:
Acoustic level:

38 dB @ 1 m | 36 dB @ 5 m

Lunghezza cavo, misure e peso:
Power cord length, dimensions and weight:

5 m | 58 x 65 x 87 cm | ~52 kg

KIT STANDARD ACCESSORI | ACCESSORIES STANDARD KIT



Tubo vapore (4 m)

Steam hose (4 m)



Valvola farfalla

Butterfly valve

ACCESSORI OPTIONAL CONSIGLIATI | SUGGESTED OPTIONAL ACCESSORIES



**Tubi vapore
(6-8-10 m)**

Steam hose
(6-8-10 m)



**Attacchi
Garolla-DIN-Triclamp**

Garolla-DIN-Triclamp
attaches



**Diffusore per barrique con maniglia
con attacco Garolla-DIN-Triclamp**

Steam diffuser for barrels with handle
with Garolla-DIN-Triclamp attach